


313296

PCHM8FG9/1

## FREESTANDING 2-BURNERS HERMETIC GAS BOILING TOP WITH A CAST IRON GRID ON OPEN CABINET





- Freestanding 2-burner gas boiling top on an open cabinet (80x45 cm).
- High-efficiency hermetic burners, cast-iron base and brass flame spreaders with single ring 6 kW and 10 kW.
- Mosaico90 is a special line of modular units, 45 cm deep, which combine

perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.

- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is included, should conversion on site be necessary.



## TECHNICAL DATA

| TOTAL POWER             | 16 kW                    | GAS POWER                 | 16 kW         |
|-------------------------|--------------------------|---------------------------|---------------|
| OPEN BURNER POWER       | 1X6+1X10 n°- kW          | BOILING TOP POWER         | 16 kW         |
| NATURAL GAS CONSUMPTION | 1,69 m³/h                | LPG CONSUMPTION           | 1.26 kg/h     |
| CABINET DIMENSIONS      | 73X34X39,5 cm            | NUMBER OF BURNERS         | n° 2          |
| BOILING PAN SUPPORT     | RAAF enamelled cast iron | CE GAS CERTIFICATE NUMBER | CE-0085CR0045 |
| GAS CONNECTION DIAMETER | 1/2"G EN10226-1          | IPX RATING                | 4             |
| WIDTH                   | 80 cm                    | DEPTH                     | 45 cm         |
| HEIGHT                  | 90 cm                    | PACKAGE WIDTH             | 86 cm         |
| PACKAGE DEPTH           | 52 cm                    | PACKAGE HEIGHT            | 115 cm        |
| NET WEIGHT              | 44,8 kg                  | GROSS WEIGHT              | 56,8 kg       |
| VOLUME                  | 0,51 m³                  | HARMONISED CODE           | 84198180      |

SENSIBLE HEAT RELEASE

4800.0 W

## **ACCESSORIES**

LATENT HEAT RELEASE

STEAM RELEASE

1920.0 W

2816.0 g/h



## **INSTALLATION SCHEMES**

