

313297

PCHM8FG9/2

**FREESTANDING SUPER 2-BURNERS HERMETIC
GAS BOILING TOP WITH A CAST IRON GRID ON
OPEN CABINET**



- Freestanding 2-burner gas boiling top on an open cabinet (80x45 cm) (SUPER version).
- High-efficiency hermetic burners, cast-iron base and brass flame spreaders with single ring 10 kW and 11 kW.
- Mosaico90 is a special line of modular units, 45 cm deep, which combine perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is included, should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	21 kW	GAS POWER	21 kW
OPEN BURNER POWER	1X10 + 1X11 n°- kW	BOILING TOP POWER	21 kW
NATURAL GAS CONSUMPTION	2,22 m³/h	LPG CONSUMPTION	1.65 kg/h
CABINET DIMENSIONS	73X34X39,5 cm	NUMBER OF BURNERS	n° 2
BOILING PAN SUPPORT	RAAF enamelled cast iron	CE GAS CERTIFICATE NUMBER	CE-0085CR0045
GAS CONNECTION DIAMETER	1/2"G EN10226-1	GAS CONNECTION HEIGHT (H)	486 mm
GAS CONNECTION HEIGHT (X)	122 mm	GAS CONNECTION HEIGHT (Y)	-45 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	80 cm
DEPTH	45 cm	HEIGHT	90 cm
PACKAGE WIDTH	87 cm	PACKAGE DEPTH	54 cm
PACKAGE HEIGHT	116 cm	NET WEIGHT	44,3 kg
GROSS WEIGHT	56,8 kg	VOLUME	0,55 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	2520.0 W
SENSIBLE HEAT RELEASE	6300.0 W	STEAM RELEASE	3696.0 g/h

ACCESSORIES

319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319067	10KW HERMETIC FLAME SPREADER
719007	PAIR OF CLOSING ELEMENTS (L=45CM)

INSTALLATION SCHEMES

