

**313298**

PCHM12FG9/1

**FREESTANDING 3-BURNERS HERMETIC GAS  
BOILING TOP WITH A CAST IRON GRID ON OPEN  
CABINET**



- Freestanding 3-burner gas boiling top on an open cabinet (120x45 cm).
- High-efficiency hermetic burners, cast-iron base and brass flame spreaders with 1 single ring (6 kW) and 2 double ring (10,0 kW).
- Mosaico90 is a special line of modular units, 45 cm deep, which combine perfectly with the Tecno90 range to create compact cooking islands designed to make the best use of space.
- AISI 304 stainless steel worktop (20/10 thick) with Scotch Brite finish, set up for internal coupling without external joints.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktops with rounded corners and overflow-proof grooves for maximum hygiene and easy cleaning.
- Main burner ignition by means of a pilot burner with safety thermocouple.
- Valved gas cock.
- Enamelled cast iron pan support grid to resist acids, alkalis and flames.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- The gas appliances are certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is included, should conversion on site be necessary.

---

## TECHNICAL DATA

|                           |                          |                           |               |
|---------------------------|--------------------------|---------------------------|---------------|
| TOTAL POWER               | 26 kW                    | GAS POWER                 | 26 kW         |
| OPEN BURNER POWER         | 1X6 + 2X10 n° - kW       | BOILING TOP POWER         | 26 kW         |
| NATURAL GAS CONSUMPTION   | 2,76 m³/h                | LPG CONSUMPTION           | 2.05 kg/h     |
| CABINET DIMENSIONS        | 113X34X39,5 cm           | NUMBER OF BURNERS         | n° 3          |
| BOILING PAN SUPPORT       | RAAF enamelled cast iron | CE GAS CERTIFICATE NUMBER | CE-0085CR0045 |
| GAS CONNECTION DIAMETER   | 1/2"G EN10226-1          | GAS CONNECTION HEIGHT (H) | 486 mm        |
| GAS CONNECTION HEIGHT (X) | 122 mm                   | GAS CONNECTION HEIGHT (Y) | -45 mm        |
| FOOT HEIGHT               | 133 mm                   | FOOT ADJUSTMENT           | 133/195 mm    |
| IPX RATING                | 4                        | WIDTH                     | 120 cm        |
| DEPTH                     | 45 cm                    | HEIGHT                    | 90 cm         |
| PACKAGE WIDTH             | 126 cm                   | PACKAGE DEPTH             | 53 cm         |
| PACKAGE HEIGHT            | 115 cm                   | NET WEIGHT                | 68 kg         |
| GROSS WEIGHT              | 79,5 kg                  | VOLUME                    | 0,76 m³       |
| HARMONISED CODE           | 84198180                 | LATENT HEAT RELEASE       | 3120.0 W      |
| SENSIBLE HEAT RELEASE     | 7800.0 W                 | STEAM RELEASE             | 4576.0 g/h    |

---

## ACCESSORIES

|        |                                                                       |
|--------|-----------------------------------------------------------------------|
| 319002 | STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90 |
| 319067 | 10KW HERMETIC FLAME SPREADER                                          |
| 319068 | HERMETIC FLAME SPREADER (5 - 6 - 7 KW)                                |
| 719007 | PAIR OF CLOSING ELEMENTS (L=45CM)                                     |

INSTALLATION SCHEMES

