

316169

FRD81FE9

FREESTANDING DOUBLE TANK 21+21L ELECTRIC FRYER, ELECTRONIC CONTROL AND IN-TANK ROTATING HEATING ELEMENTS ON CLOSED CABINET - BASKETS, LIDS AND OIL DRAINING TANK INCLUDED



- Electric fryer with electronic control and 2 tanks 21+21 L on a closed cabinet (80 cm).
- Power: 2x20 kW.
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Deep drawn worktop with a seamlessly welded AISI 304 deep drawn cooking tank, featuring rounded corners.
- The electronic control allows for greater precision between the set temperature and the temperature in the tank.
- Cooking programmes can be saved, thus creating standardised recipes.
- The Melting programme enables solid fats like butter, lard, and stored frying oils to melt without the risk of burning.
- Large front basin and front zone for oil and foam expansion.
- Heating through AISI 304 stainless steel rotating armoured heating elements for easy cleaning of the tank and worktop.
- \bullet Operating thermostat ranging between 100°C and 190°C below oil smoke point.
- Bulb thermostats immersed in oil are more efficient in sensing the temperature inside the tank, promptly adjusting the oil to the desired temperature, minimising smoke points, and prolonging the oil life.
- A safety thermostat triggers in case of abnormal operation.
- Draining on the tank bottom.
- Tank with a filter for collecting oil inside the cabinet, baskets and lids included.
- Basket support fixed to the rear part of the worktop.
- Technical compartment for easy connection to the electrical network.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).



TECHNICAL DATA

TOTAL POWER	40 kW	ELECTRIC POWER	40 kW
FREQUENCY	50/60 Hz	VOLTAGE	400 3N ~ V
TEMPERATURE RANGE	140÷190 °C	TANK CAPACITY	21lt+21lt
TANK DIMENSIONS	30,7x46x25,7 cm	HEATING	Heating elements in the tank

MINIMUM POWER CABLE 5 x 10 n° - mm² ELECTRIC CABLE TYPE H07 RN-F

CROSS-SECTION

TANKS n° 2 **ELECTRICAL CONNECTION** -640 mm HEIGHT (Y)

FOOT HEIGHT FOOT ADJUSTMENT 133 mm

133/195 mm **IPX RATING** WIDTH 80 cm DEPTH **HEIGHT** 90 cm 90 cm PACKAGE WIDTH PACKAGE DEPTH 86 cm 100 cm PACKAGE HEIGHT 112 cm **NET WEIGHT** 83 kg **GROSS WEIGHT** 101 kg **VOLUME** 0,96 m³ HARMONISED CODE 84198180 LATENT HEAT RELEASE 28000.0 W SENSIBLE HEAT RELEASE 3600.0 W STEAM RELEASE 41200.0 g/h

ACCESSORIES

319010	REAR COVERING PANEL FOR CABINET (L=80CM)
399546	EXTRA OIL COLLECTION TANK FOR FRYERS (21L)
000570	DAID OF OLOOPING ELEMENTO FOR DAGED AND MODIFICADO

PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM) 399573

2 EXTRA FRYER BASKETS (21L) - DIM. CM (14X41X12H) 399580 399581 EXTRA FRYER BASKET (21L) - DIM. CM (28.5X41X12H)



INSTALLATION SCHEMES

