
316255

FTL12FE9

**FREESTANDING ELECTRIC GRIDDLE WITH
SMOOTH PLATE ON OPEN CABINET**



- Freestanding electric griddle with a smooth steel cooking plate on an open cabinet (120 cm).
- The cooking plate, recessed and hermetically welded to the worktop, allows you to cook large quantities of different foods.
- 3 stainless steel burners (6 kW) with 3 independent working zones.
- AISI 304 stainless steel height-adjustable feet (133/195 mm).
- AISI 304 stainless steel 2mm thick worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Equipment intended for direct cooking of food, use for heating pots or pans is not permitted.
- Deep drawn worktop with a hermetically welded recessed cooking plate, featuring large cooking area with rounded corners for enhanced hygiene and easy cleaning.
- Heating through stainless steel armoured heating elements.
- Operating thermostatic valve with temperature control ranging between 70°C and 300°C.
- Equipped with a safety thermostat that triggers in case of abnormal operation.
- Sloped cooking plate (15 mm thick) to drain grease and liquids.
- Heating and control commands specific for each zone.
- Removable liquid and grease collection drawer with overflow hole.
- Removable splashback on 3 sides and cap included.
- Technical compartment for easy connection to the electrical network.

TECHNICAL DATA

TOTAL POWER	18 kW	ELECTRIC POWER	18 kW
FREQUENCY	50/60 Hz	VOLTAGE	380-415 3N~ V
TEMPERATURE RANGE	60÷270 °C	CABINET DIMENSIONS	113x76,1x39,5 cm
MINIMUM POWER CABLE CROSS-SECTION	5 x 4 n° - mm ²	COOKING SURFACE	113x69 cm
ELECTRIC CABLE TYPE	H07 RN-F	PLATE TYPE	Smooth
HEATING ZONES	n° 3	ELECTRICAL CONNECTION HEIGHT (H)	660 mm
ELECTRICAL CONNECTION HEIGHT (X)	1121 mm	ELECTRICAL CONNECTION HEIGHT (Y)	-75 mm
FOOT HEIGHT	133 mm	FOOT ADJUSTMENT	133/195 mm
IPX RATING	4	WIDTH	120 cm
DEPTH	90 cm	HEIGHT	90 cm
PACKAGE WIDTH	126 cm	PACKAGE DEPTH	100,0 cm
PACKAGE HEIGHT	116 cm	NET WEIGHT	196 kg
GROSS WEIGHT	211 kg	VOLUME	1,46 m ³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	7200.0 W
SENSIBLE HEAT RELEASE	5940.0 W	STEAM RELEASE	10584.0 g/h

ACCESSORIES

120595	GRIDDLE-CLEANING SCRAPER
120597	SCRAPER - SPARE BLADE KIT (10 PCS)
319002	STAINLESS STEEL RH/LH DOOR FOR TECNO74, TECNO90, MOSAICO74, MOSAICO90
319009	REAR COVERING PANEL FOR CABINET (L=40CM)
399573	PAIR OF CLOSING ELEMENTS FOR BASES AND WORKTOPS (L=90CM)

INSTALLATION SCHEMES

