

713194

PCH4G7

2-BURNER HERMETIC GAS BOILING TOP WITH CAST IRON GRID (TOP VERSION)



- 2-burner gas boiling top (40 cm).
- High-efficiency hermetic burners, cast-iron base and brass flame spreader with power 5 kW and 7,5 kW
- Deep drawn worktop with rounded corners to avoid overflow and for maximum hygiene and easy cleaning.
- Main burner ignition via always-on pilot burner with safety thermocouple.
- Valved gas cock.
- Setup for installing a water tap.
- Enamelled cast iron pan support grid to resist acids, alkalis and flames.
- Height-adjustable rubberised plastic feet (15-25 mm).
- AISI 304 stainless steel worktop and Scotch Brite finish with internal side-by-side joining system.
- AISI 304 stainless steel control panel and side panels.
- Technical compartment to facilitate connection to the gas network.
- The gas appliances are CE-certified by German body DVGW and have passed the most stringent safety tests.
- The supply of the equipment follows the customer's wishes in terms of nozzles installed, even during the testing phase. The standard configuration is G20 natural gas. In addition, a set of nozzles is supplied should conversion on site be necessary.

TECHNICAL DATA

TOTAL POWER	12,5 kW	GAS POWER	12,5 kW
ELECTRIC POWER	- kW	OPEN BURNER POWER	1x5 + 1x7,5 n° - kW
BOILING TOP POWER	12,5 kW	NATURAL GAS CONSUMPTION	1,32 m³/h
LPG CONSUMPTION	0.99 kg/h	NUMBER OF BURNERS	n° 2
BOILING PAN SUPPORT	RAAF enamelled cast iron	GAS CONNECTION DIAMETER	1/2"G EN10226-1
GAS CONNECTION HEIGHT (H)	35 mm	GAS CONNECTION HEIGHT (X)	366 mm
GAS CONNECTION HEIGHT (Y)	-63 mm	FOOT HEIGHT	15 mm
FOOT ADJUSTMENT	15/25 mm	WIDTH	40 cm
DEPTH	70 cm	HEIGHT	28 cm
PACKAGE WIDTH	81,0 cm	PACKAGE DEPTH	47,0 cm
PACKAGE HEIGHT	55 cm	NET WEIGHT	29,2 kg
GROSS WEIGHT	34,6 kg	VOLUME	0,21 m³
HARMONISED CODE	84198180	LATENT HEAT RELEASE	1500.0 W
SENSIBLE HEAT RELEASE	3750.0 W	STEAM RELEASE	2200.0 g/h

ACCESSORIES

319068	HERMETIC FLAME SPREADER (5 - 6 - 7 KW)
719043	STAINLESS STEEL SIDE PANEL T74 L=71CM
719044	OVERHEAD STAINLESS STEEL SHELF STRUCTUREWITH 2 SIDE PANELS FOR T74 L=200CM
719045	OVERHEAD STAINLESS STEEL SHELF STRUCTUREWITH 2 SIDE PANELS FOR T74 L=240CM
719046	OVERHEAD STAINLESS STEEL SHELF STRUCTUREWITH 2 SIDE PANELS FOR T74 L=280CM
719047	OVERHEAD STAINLESS STEEL SHELF STRUCTUREWITH 2 SIDE PANELS FOR T74 L=320CM
719048	OVERHEAD STAINLESS STEEL SHELF STRUCTUREWITH 2 SIDE PANELS FOR T74 L=360CM

INSTALLATION SCHEMES




Fig.1 | Abb.1 | рис.1 - 5415.649.00